

Description

auxi-L is a KS-BUS expansion module with 5 relay outputs rated at 8 A, featuring a common changeover contact that greatly simplifies wiring. It is the ideal module for managing lights and loads.

Each output can be programmed as N.C., N.O., bistable, or monostable. It connects to lares 4.0 through the 4-wire KS-BUS serial bus, and terminal programming is carried out directly from the Installer web server interface.

System configuration is extremely fast: auxi-L is automatically acquired by lares 4.0 and uniquely identified by the 6-digit serial number printed on the label attached to the board.



KSI2300004.300

Its compact dimensions allow it to be installed inside DIN 503 flush-mount boxes or, alternatively, the slim plastic enclosure (Ksenia code KSI7302000.010), which can accommodate up to 2 expansion modules, can be used.

Technical Specifications

Power supply:	13,8 Vcc
Current consumption:	120 mA max
Relais outputs:	5, 250 V - 8A (10A peak)
Operating temperature:	from +5°C to +40°C
Humidity:	95%
Dimensions:	75 × 45 × 16 mm (W x H x D)
Weight:	100 gr.

System maximum configuration

lares 4.0 models	wls 96	16	40	40 wls	140 wls	644 wls
Maximum number of BUS expansion modules	6	4	24	24	64	200

Compliance

- Europe - CE, RoHS



How to order

KSI2300004.300 - module auxi-L

Accessories



KSI7300000.001 - Plastic box for DIN rail



KSI7302000.010 - Slim plastic box for up to 2 modules

Technical specification, appearance, functional and other product characteristics may change without notice.